

## Sign Stencil Products



**116**

A high-tack computer stencil for use on raw wood surfaces and urethane foamboard. 15-inch features trimmed edges and a strong, clear film liner that offers easy alignment and smooth, precise running on computerized sign-making machines. The 30-inch width tracks only on large pin plotters and the stencil rubber extends to the edge of the liner. CAUTION: 116 has a very aggressive adhesive and is not recommended for use on some woods without first testing a sample piece. Do not use on preprinted, pretreated or glass surfaces.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
116	15, 30	10	H	33	S		15	15, 30	15



**117**

Designed for use with computerized cutting machines. Trimmed edges on 15-inch roll allows smooth and easy tracking through the machine. A strong, clear film liner provides extra rigidity. The 15-inch width will track through most computer cutters. The 30-inch width will track only through a large pin plotter and the stencil rubber extends to the edge of the liner. After letters and designs are cut, they must be taped for transferring the stencil to stone. Use with Intertape™/ Anchor Filler #211.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
117	15, 30	10	M	33	S		15	15, 30	15



**120**

A multi-purpose, medium-tack stencil designed for shape and depth carving in glass and pretreated, preprinted or soft woods. Extremely easy to hand cut. Dark blue release liner lifts away easily. Stencil holds securely during blasting. No fillers are required saving time on application and cleanup. 120 can also be used on tile, pretreated urethane foamboard and plexiglass. Available in 25-inch width only.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
120	25	10	M	33	S	•			

**125**

A high-tack stencil designed for sandblasting on raw wood and urethane foamboard. Easy-release orange liner. The strength of the adhesive eliminates the need for filler or spray adhesives. CAUTION: This stencil has a very aggressive adhesive and is not recommended for use on some woods without first testing a sample piece. Do not use on prepainted, pretreated or glass surfaces. Size available: 25-inch width only.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
125	25	10	H	36	S	•			

**128**

This 18-mil hand cut stencil is designed for glass etching, and can also be used on light stone, tile, and acrylic etching. The paper liner removes easily. Has a petroleum-based adhesive system and conforms nicely to curved or irregular surfaces. Available in 25-inch and 30-inch widths. All rolls are 10 yards in length. Use with Intertape™/Anchor Filler #211.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
128	25, 30 1/2	10	M	20	S		•		

**153**

For use on friction-fed cutters. Can be used safely on pretreated and prepainted wood, urethane foamboard, glass, tile and acrylic. Rubber is trimmed back 1/2-inch along each edge so the wheels can clamp down on the 5-mil polyester film liner and carry the stencil through the computer. Since this type of plotter has no sprockets, holes are unnecessary (as in other computer stencils). Sizes available: 19 7/8-inch and 24-inch widths.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
153	19 7/8, 24	10	M	33	S		•		



**156**

Same construction as our high-tack 116 computer stencil, except that the hole pattern is for use on standard ½-inch on center sprocket machines and edges are trimmed. Available in 30-inch width. CAUTION: 156 has a very aggressive adhesive and is not recommended for use on some woods without first testing a sample piece. Do not use on preprinted, pretreated or glass surfaces. Note: 156 will not work on the large pin 30-inch plotter; style 116 is recommended for this use.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
156	30	10	H	33	S		•		•



**157**

Same construction as our medium-tack 117 computer stencil, except that the hole pattern is for use on standard ½-inch center sprocket system machines and edges are trimmed. Available in 30-inch width. Note: 157 will not work on the large pin 30-inch plotter; style 117 is recommended for this use.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
157	30	10	M	33	S		•		•



**T226**

High-tack BlastLite™ is a specially-formulated rubber mask that is long-lasting and easy to use. Natural flexibility properties and impact resistance makes it ideal for all substrates where shallow blasting is required. BlastLite™ High-tack Stencils are coated with an acrylic adhesive for use on raw wood, unprimed HDU, brick or unglazed tile. Available unpunched or friction fed.

Product Specifications						Cutting Methods			
Product Number	Width (n.)	Length (yds.)	Adhesive Tack	Average Thickness (mils - w/o liner)	Single/Double Liner	Hand Cut	Friction Fed	Sprocket Fed Gerber Punch	Sprocket Fed 1/2" O.C. Punch
T226	15, 20, 25, 30	10	H	22	S	•			